

North America's #1 Brand of High-Pressure Cleaning Equipment

800 Series

Electric / Belt Drive

U.S. Design Patent No. 726,382 S

Hot-Water Pressure Washers

Upright, oil fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

50-ft. length of high-pressure hose for ease in cleaning around a large area Reliable, energy efficient **oil burner** is built to provide years of trouble free service

Hose-reel slot accepts swivel or stationary reels for ease in hose management and storage Simple, easy-to-use control panel includes adjustable thermostat **Pressure relief valve** protects the machine and user from thermal expansion

Stainless-steel coil skin provides extra durability to withstand the elements

Adjustable upstream detergent injection

ensures high-pressure

On board **wand and**

12" solid rubber tires for easy maneuvering; eliminates risk of flats

cord storage

sudsing for better cleaning

Protective cabinet contains water resistant electical box

Float tank helps maintain constant water pressure and flow while helping to prevent sediment from entering the machine's components

Forklift slots for easy lifting

Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap

> **Wide wheel base** for stability, but 28" width easily fits through doors

FEATURES

- 4.0 5.0 GPM @ 2000 to 3000 PSI
- Oil Fired Burner
- 208V, 230V, 460V or 575V, 1PH or 3PH

Belt Drive Hotsy Pump

Easily removable **cover** provides protection and easy access to components

Heater coil carries a 5-year warranty



원 초

Beefy casters for easy movement

35-ft. power cord with safety **Ground Fault Circuit Interrupter** (GFCI breaker) *single phase only



Hotsy-designed Triplex pumps carry a 7-year limited warranty

www.Hotsy.com

Nothing Cleans Like a Hotsy!

Oil-Fired 4.0 - 5.0 GPM @ 2000 to 3000 PSI Hotsy 7-Year Pump Warranty

Belt Drive

Rugged design, easy maneuverability and massive cleaning power!

SPECIFICATIONS BELT DRIVE											
MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	BTU/HR	PUMP MODEL	HOSE	SHIP WT
821	4.0	2300	6.2	3450	208/1	33	Oil	381,000	HM4045R.3	50′	632
842	4.0	2000	5	1725	208/3	20	Oil	381,000	HM4030R.3	50′	622
843	4.0	2000	5	1725	230/1	29	Oil	381,000	HM4030R.3	50′	622
844	4.0	2000	5	1725	230/3	19	Oil	381,000	HM4030R.3	50′	622
845	4.0	2000	5	1725	460/3	10	Oil	381,000	HM4030R.3	50'	691
851	4.0	3000	8.2	3450	208/1	44	Oil	381,000	HM4045R.3	50′	675
852	4.0	3000	7.5	1725	208/3	25	Oil	381,000	HM4030R.3	50′	665
853	4.0	3000	7.5	1725	230/1	37	Oil	381,000	HM4030R.3	50'	665
854	4.0	3000	7.5	1725	230/3	25	Oil	381,000	HM4030R.3	50′	665
855	4.0	3000	7.5	1725	460/3	14	Oil	381,000	HM4030R.3	50′	665
856	4.0	3000	8.2	3450	575/3	11	Oil	381,000	HM4045R.3	50'	680
873	5.0	3000	10	1725	230/1	42	Oil	404,000	HM4030R.3	50′	670
874	5.0	3000	10	1770	230/3	29	Oil	404,000	HM4030R.3	50′	675

Dimensions: 51" | x 28" w x 51" h

DON'T FORGET THE SOAP!

Hotsy pressure washers clean best when matched with specially formulated Hotsy detergents. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. All are highly concentrated, so a little goes a long way.

ANDY.

HOTSY SOLUTION SELECTOR What's the best detergent for your next job? Find out with our solution selector. Scan this QR code or visit HOTSY.com

SERVICE & REPAIR

Hotsy has more than 175 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Hotsy has factory-trained service technicians who will provide on-site maintenance for your cleaning equipment. Our techs have most common replacement parts on their service truck, and will quickly have your washer running smoothly.



OPTIONS FOR 800 SERIES

- 8" Oil-Fired Draft Diverter barometric; prevent backdraft; keeps cold air out
- Auto Start / Stop, Thermal Shutdown or Time Delay Shutdown
- Hose Reels, Hose Reel Brackets and Detergent Bracket

PARTS & ACCESSORIES

Your local Hotsy dealer would be happy to provide an onsite demonstration to determine which pressure washer accessories will help speed cleaning and lower your costs. Hotsy dealers stock thousands of pressure washer replacement parts such as high pressure hose, trigger guns, high pressure nozzles, pumps, engines, motors, unloaders, filters and wands. In addition, you'll find a number of accessories designed to speed cleaning, the most common accessories are telescoping wands, pivot and non-pivot hose reels, flat surface cleaners and high

pressure turbo nozzles.

FIND OUT MORE ONLINE: HOTSY.COM

Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631 www.Hotsy.com email:info@Hotsy.com P/N 9.801-490.0 / HOT_800 Effective 03/20 Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© KÄRCHER North America ©2020 Hotsy NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models.

Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at \pm 10% and in some cases are tighter within \pm 5% of listed specifications.