

IB 10/8 L2P

The IB 10/8 L2P is the world's first dry ice blaster with integrated dry ice production from liquid CO₂. Perfect for short-term cleaning applications, without complicated logistics.



Order no. 1.574-200.0

- With integrated dry-ice production
- Compact, mobile design and easy operation
- Low compressed air consumption for use of workshop compressors

Technical data

EAN code		4054278294247
Connected load	kW	1
Compressed air connection		1/4" quick coupling
Casing / frame		Plastic rotation body
Certified (by) to		CE
Cable length	m	5.5
Air pressure	bar / MPa	0.7 - 10 / 0.07 - 1
Air quality		Dry & oil-free
Air flow	m³/min	0.07 - 0.8
Sound pressure level	dB(A)	95
Dry ice pellets (diameter)	mm	2.5
Dry ice consumption	kg/h	2 - 8
Liquid CO₂ consumption	kg/h	20 - 60
Number of current phases	Ph	1
Frequency	Hz	50 - 60
Voltage	V	220 - 230
Weight without accessories	kg	92
Weight (with accessories)	kg	103.6
Dimensions (L × W × H)	mm	870 × 450 × 970

Equipment

Flat jet nozzle, short	■
Spray hose with electrical control cable and quick coupling	■
Jet gun (ergonomic and safe)	■
"Air only" or "Air and ice" switch on the trigger gun	■
Electronic control system	■

■ Included in the scope of supply.

Users must receive training on this device.



Ergonomic blasting gun

- Quick and easy nozzle change thanks to quick-release couplings.
- With integrated lighting.
- Ice on/off switch directly on the trigger gun.



Easy and intuitive operation


- Jet pressure, operating hours, service time shown on the display.
- Dry-ice quantity can be adjusted with a button.
- Integrated status display and assistance systems, e.g. for pressure monitoring.



Safe dry-ice blasting

- CO₂ is discharged via exhaust hose.
- Safe handling, no contact with the dry-ice pellets.
- Self-locking gun trigger.

ACCESSORIES FOR IB 10/8 L2P 1.574-200.0



		Order no.	Description	
COMPACT CLASS				
Blast nozzles				
Flat jet nozzle short, standard, dia. 3 mm	1	4.574-094.0	Short flat jet nozzle for dry ice cleaning systems from Kärcher. Perfect for gently cleaning delicate surfaces and hard-to-reach areas. With quick-change system.	■
Flat jet nozzle short, power, dia. 3 mm	2	4.574-117.0	Perfect for abrasive applications in hard-to-reach places, short power flat jet nozzle for use with dry ice cleaning systems from Kärcher. With quick-change system.	■
Long flat jet nozzle, dia. 3 mm	3	4.574-083.0	Long, sturdy, rotatable power flat jet nozzle for use with dry ice cleaners from Kärcher. Features quick-change system and is also particularly well-suited to abrasive applications.	□
Round spray nozzle, long, dia. 3 mm	4	4.574-105.0	Long power round jet nozzle for dry ice cleaning systems from Kärcher. For abrasive applications, such as removing stubborn encrustations, paint, oil or soot. With quick-change system.	□
Blasting gun				
Hand trigger gun	5	4.574-067.0	Ergonomic and compact jet gun for Ice Blaster dry-ice blasting system from Kärcher. Includes 5-m spray hose, nozzle light and nozzle quick-change system.	■
Spray hose extension, 5 m	6	4.574-111.0	Extension hose for L2P dry ice blasters from Kärcher. This simple spray hose extension is a straightforward, effortless way to extend the working range of the ice blaster.	□
Attachment sets and other accessories				
Holder for CO ₂ cylinder cap	7	2.574-002.0	Practical holder for holding the lids of CO ₂ cylinders during cleaning work with dry-ice blasting system in the Liquid-to-Pellet process, secures against loss.	□
Y-fitting, compressed air	8	2.574-003.0	Special Y-fitting for connecting 2 compressed air hoses with small cross-section to dry ice blasters.	□
L2P Splash Guard	9	2.574-004.0	Adjustable splash guard for cleaning work with dry-ice blasting systems in the Liquid-to-Pellet process.	□
RPV adapter	10	2.574-006.0	To increase the cleaning performance with dry-ice blasting systems: Special adapter for opening the residual pressure valve (RPV) of CO ₂ cylinders.	□
Adjust & Filter attachment kit	11	2.644-227.0	For the assembly at the Home Base of our dry ice cleaner IB 10/8 L2P: attachment kit with pressure reducer, water and oil separator. Adjustment of the jet pressure directly at the machine when required.	□
CO ₂ supply line extension, 5 m	12	4.574-144.0	Extension hose with a length of 5 m for connecting CO ₂ cylinders or cylinder bundles to dry ice blasters with integrated dry ice production (liquid-to-pellet/L2P).	□
Cylinder trolley	13	6.574-336.0	Perfect as supplement to the dry-ice blasting systems with Liquid-to-Pellet process: Cylinder trolley for the safe transport of standard CO ₂ cylinder.	□
Ring spanner wrench SW30 / SW32	14	6.574-337.0	Ring spanner with 2-in-1 function. Suitable for loosening the CO ₂ cylinder lid and for fastening the CO ₂ hose to the cylinder.	□

■ Included in the scope of supply. □ Available accessories.


ACCESSORIES FOR IB 10/8 L2P 1.574-200.0




15



16




17



18



19



20



21



22

		Order no.	Description	
OTHER ACCESSORIES SCRUBBER DRIERS				
Home Base accessories				
Home Base adapter	15	5.035-488.0	Fastener for various hooks and clips on the machine.	<input type="checkbox"/>
Universal hook kit	16	4.070-075.0	Hook and adaptor kit for attachment to the Home Base rail scrubber drier by Kärcher. Ideal for space-saving storage of hoses (for example, spray suction attachment kit) on the machine.	<input type="checkbox"/>
Double hook	17	6.980-077.0	Double hook for attaching rubbish bags, etc. to the machine. Only for use with the Homebase adapter 5.035-488.0.	<input type="checkbox"/>
Holder handhold grey	18	6.980-078.0	Mop clip for attaching a mop to the machine. Only for use with the Homebase adapter 5.035-488.0.	<input type="checkbox"/>
SPRAY EXTRACTION MACHINES				
Other				
Cleaning agent container, complete	19	4.070-006.0	Kit consisting of cleaning agent container and Home Base adapter. For connecting Home Base rail.	<input type="checkbox"/>
DRY ICE CLEANING				
Protective equipment				
Safety glasses	20	6.321-208.0	Safety goggles.	<input type="checkbox"/>
Protective gloves	21	6.321-210.0	Cold protection glove, size 10 with slip-resistant profile (Category 3 according to EN 511, Level 12X EN 388, Level 2121).	<input type="checkbox"/>
Hearing protection	22	6.321-207.0	Effective hearing protection with an average insulation rating of 35 dB(A) according to SNR (Single Number Rating).	<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.